

# ECX

# 3000


Intel® Core™ i9/i7/i5/i3 Processor (14th Gen)  
Workstation-grade Fanless Embedded System



- Workstation-grade Platform : Intel® Core™ i9/i7/i5/i3 Processor (14th gen, codename : RPL-S Refresh/RPL-S/ADL-S) running with Intel® R680E PCH supports max 65W TDP CPU
- Intel® UHD Graphics 770/730 driven by Intel® X<sup>e</sup> architecture with up to 32 graphics execution units (EUs) delivers immersive interactions with integrated graphics and accelerated AI performance
- 8 Independent 2.5G LAN with 4 IEEE 802.3at PoE<sup>+</sup>
- 4 Front-access M.2 SSD Tray, 6 USB 3.2 Gen 2
- DC 9V to 50V Power Input, Software Ignition Control
- Supports Intel® vPro, TCC, Time-Sensitive Networking (TSN), and TPM 2.0
- Optional VHub One-Stop AIoT Solution Service supports OpenVINO based AI accelerator and advanced Edge AI applications

## The Latest Edge AI Accelerator | Leading Integration Rugged Reliability | Optimized Manageability

Workstation-grade Platform : Intel® Core™ i9/i7/i5/i3 Processor (14th gen, codename : RPL-S Refresh/RPL-S/ADL-S) with Intel® R680E Chipset, fanless -40°C to 75°C operating temperature, multiple 10G LAN/2.5G LAN/GigE LAN/SIM socket configuration, max 6 USB 3.2 Gen 2 connections supporting up to 10Gbps data rate, outstanding system performance, 5G/WiFi 6/4G/3G/LTE/GPRS/UMTS mobile availability, DC 9V to 50V power input. With software ignition power control, rugged reliability in harsh environments, and all-in-one integrated features, the ECX-3000 Series Fanless Embedded System is your new generation choices for Machine Vision, In-vehicle Computing, Public Security, Factory Automation, Intelligent Transportation System (ITS), Robotic Control, AMR/AGV, Deep Learning, and any Edge AI applications.



OpenVINO™



# Specifications

## System

Processor	- 24-core Intel® Core™ i9/i7/i5/i3 Processor (14th gen, Raptor Lake-S Refresh) - 24-core 13th Gen Intel® Core™ i9/i7/i5/i3 Processor (Raptor Lake-S) - 16-core 12th Gen Intel® Core™ i9/i7/i5/i3 Processor (Alder Lake-S)
Chipset	Intel® R680E Chipset
BIOS	AMI
SIO	IT8786E
Memory	2 DDR4 3200MHz SO-DIMM, up to 64GB
OS	Windows 11, Windows 10, Linux

## I/O Interface

Serial	Up to 4 COM RS-232/422/485
USB	6 USB 3.2 Gen 2
Isolated DIO	16 Isolated DIO : 8 DI, 8 DO (Optional)
LED	Power, HDD, PoE, Wireless
SIM Card	2 External SIM Card Sockets
RTC Battery	Front-access RTC Battery

## Expansion

Mini PCIe	1 Mini PCIe Socket for PCIe/USB/SIM Card/Optional mSATA
M.2	- 1 M.2 Key B Socket (3042/3052, SATA/USB 3, default/USB 2) - 1 M.2 Key E Socket (2230, PCIe x2/USB)
SUMIT	- 2 SUMIT Slot (Optional)

## Graphics

Graphics Processor	Intel® UHD Graphics 770/730 driven by Intel® X® Architecture
Interface	4 independent displays : - 2 DisplayPort : Up to 7680 x 4320 @60Hz/5120 x 2880 @60Hz - 1 DVI-I : Up to 1920 x 1080 @60Hz - 1 HDMI : Up to 1920x1080 @60Hz

## Storage

SATA	2 SATA III (6Gbps) support S/W RAID 0, 1
mSATA	1 SATA III (Mini PCIe Type, 6Gbps)
M.2	1 M.2 Key M Socket (2280, PCIe x4)
Storage Device	- 2 Front-access 2.5" SSD/HDD Tray - 4 Front-access M.2 Key M SSD Tray ( <b>ECX-3000 PoES</b> )

## Audio

Audio Codec	Realtek® ALC888S-VD, 7.1 Channel HD Audio
Audio Interface	1 Mic-in, 1 Line-out

## Ethernet

LAN 1	Intel® I219LM GigE LAN supports iAMT
LAN 2	Intel® I226 2.5GigE LAN supports TSN

## 2.5G PoE

LAN 3 to LAN 6	2.5GigE IEEE 802.3at (25.5W/48V) PoE <sup>+</sup> by Intel® I226
----------------	--

## 2.5G Ethernet (ECX-3025R/3025)

LAN 7 to LAN 9	Intel® I225 2.5GigE LAN
----------------	-------------------------

## 10G Ethernet (ECX-3071XR/3071X)

LAN 7 to LAN 8	Intel® X710-AT2 10GigE LAN
----------------	----------------------------

## Power

Power Input	DC 9V to 50V
Power Interface	- 3-pin Terminal Block : V+, V-, Frame Ground - 4-pin Mini-DIN
Ignition Control	16-mode Software Ignition Control
Remote Switch	3-pin Terminal Block

## Others

TPM	Infineon SLB9670 supports TPM 2.0, SPI Interface
Watchdog Timer	Reset : 1 to 255 sec./min. per step
Smart Mgmt.	Wake on LAN, PXE supported
HW Monitor	Monitoring temperature, voltages. Auto throttling control when CPU overheats.

## Mechanical

Dimensions	260.0mm x 175.0mm x 79.0mm (10.24" x 6.89" x 3.11")
Weight	3.8 kg (8.38 lb)
Mounting	- Wallmount by mounting bracket - DIN Rail Mount (Optional) - 2U Rackmount (Optional)
Vibration	- IEC 60068-2-64 - SSD : 5Grms, 5Hz to 500Hz, 3 Axis
EMC	CE, FCC, EN50155, EN50121-3-2

## Environment

Operating Temp.	<b>35W TDP CPU</b> : -40°C to 75°C (-40°F to 167°F), Fanless
	<b>65W TDP CPU</b> : -40°C to 55°C (-40°F to 131°F), Fanless
	<b>ECX-3025R/ECX-3025</b> : -40°C to 70°C (-40°F to 158°F), Fanless
	<b>ECX-3071X/ECX-3071XR</b> : -25°C to 50°C (-13°F to 122°F), with Internal Fan
	<b>ECX-3000-PoES</b> : -40°C to 55°C (-40°F to 131°F), Fanless

## Environment (cont.)

Storage Temp.	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% Humidity, non-condensing
Relative Humidity	95% @75°C
Shock	- IEC 60068-2-27 - SSD : 50G @wallmount, Half-sine, 11ms

\*Environmental ratings for base system only.

## Order Information

Model	LAN			GigE	COM	SSD Tray		Isolate DIO (GPIO)
	10G	2.5G	2.5G PoE <sup>+</sup>			M.2	2.5"	
ECX-3025R	-	8	4	1	2	-	2	16
ECX-3025	-	8	4		2	-	-	16
ECX-3000-PoER	-	5	4		4	-	2	16
ECX-3000-PoES	-	5	4		4	4	-	16
ECX-3000-PoE	-	5	4		4	-	-	16
ECX-3000-4R	-	3	-		4	-	2	(16)
ECX-3000-4G	-	3	-		4	-	-	(16)
ECX-3000-2R	-	1	-		4	-	2	(16)
ECX-3000-2G	-	1	-		4	-	-	(16)
ECX-3071XR	2	5	4		2	-	2	16
ECX-3071X	2	5	4		2	-	-	16

\* Fan sink modules for ECX-3000 Series are optional. Please contact our sales team if needed.  
\* ECX-3071X Series requires internal fan

## CPU List

Series	CPU	Cores	GHz	TDP (W)	CPU	Cores	GHz	TDP (W)	ECC
Intel® Core™ (14th Gen)*	i9-14900	24	5.8	65	i9-14900T	24	5.5	35	Y
	i7-14700	20	5.4		i7-14700T	20	5.2		
	i5-14500	14	5		i5-14500T	14	4.8		
	i3-14100	4	4.7		i3-14100T	4	4.4		
Intel® Core™ (13th Gen)	i9-13900E	24	5.2		i9-13900TE	24	5		
	i7-13700E	16	5.1		i7-13700TE	16	4.8		
	i5-13500E	14	4.6		i5-13500TE	14	4.5		
	i3-13100E	4	4.4		i3-13100TE	4	4.1		
Intel® Core™ (12th Gen)	i9-12900E	16	5		i9-12900TE	16	4.8		
	i7-12700E	12	4.8		i7-12700TE	12	4.7		
	i5-12500E	6	4.5		i5-12500TE	6	4.3		
	i3-12100E	4	4.2		i3-12100TE	4	4		

\* 14th Gen support PC Client use condition only.

## Dimensions & Drawing

Unit : mm (inch)

